

Magnetic Oil Drain Plug





034Motorsports new magnetic oil drain plugs are CNC machined from 304 stainless steel. These are a direct replacement designed to fit perfectly. The permanently mounted Neodymium magnet will remove any ferrous debris circulating through the lubrication system to help ensure a long life from the engine.

Installation Spiciness Rating: MILD









Installation of your 034Motorsport Magnetic Oil Drain Plug is a straightforward process that will take approximately 30 minutes to complete.

Supplied Parts:

- (1x) 034 Magnetic Oil Drain Plug
- (2x) M12 O-rings
- (10x) Aluminum crush washers

Tools Needed:

- 13mm Socket
- 5mm Allen
- Drain tray

Getting Started

Confirm you have received all the parts included with your purchase by reading the complete guide, if there are missing components, please contact:

customerservice@034motorsport.com

About This Guide

This Install Guide documents the installation process on a Mk7 VW Golf R and a B7 Audi A4. There may be minor differences depending on specific vehicle, market, options, etc.



Install Steps

Step 1

Lift the car to access the underside of the car.



Step 2Locate the oil drain plug.



Step 3

Using a 17mm socket, remove the oil drain plug.

Step 4

Drain the oil from the oil pan.

Steps 5 & 6

Add an o-ring to the base of the threads on the plug. Install the crush washer. Make sure the o-ring is pressed inside the washer, preventing it from misaligning.







Step 7

Using a 13mm socket, install the oil drain plug with an aluminum washer. **Torque to 30Nm.**



Step 8

Add oil back into the engine.

Step 9

Lower the car back down and you are good to go.

